

	Route (Flex Auger™)	Circuit (Discaflex™)
Transport capacity		
FA 90 350–450 rpm	1700 lb/h – 4080 lb/h*	
Discaflex™		440–660 lb/h*
Number of FA/DF after weigher-mixer	30	5
Max. number of routes	20 (max. 20 sections per route)	
Max. number of circuits		5 with 1 DF/circuit
Number of feed sorts		20
Number of feeding places		496
Max. number of feed curves		30 with 20 breakings/curve
Opening outlets		24 V DC Automatic (manual override possible)
Max. number of feeding times		8
Graphic display		4.6" x 3.5" – 1/4 VGA
Backup		yes with memory card and PC
Feeding program		dosing and/or registration
Weigher-mixer with linear motor	26.4 gal	52,8 gal
Number of load cells	2	2
Capacity and precision**	143 lb ± 0.02 %	287 lb ± 0.02 %
Adjustable distribution speed to weigher-mixer/feed sort		yes
Max. number of clocks for miscellaneous applications (water, light,...)		20
Connection to PC / Internet		yes
Possible to integrate in central control panel		yes
<p>* In combination with switch valve and depending on number of ingredients and the selected mixing time.</p> <p>** Based on a specific weight of 41 lb/ft³.</p>		