

Model		50	60	70
Supply/return water temperature (°C)		80/65	80/65	80/65
Air volume (m ³ /h)		7400	7400	7400
Current (A)	230 V	2.9	2.9	2.9
	400 V	1.3	1.3	1.3
Power consumption (W)	230 V	590	590	590
	400 V	600	600	600
Supply voltage (V)		1x230/ 3x400	1x230/ 3x400	1x230/ 3x400
Rotation speed (RPM)	230 V	915	915	915
	400 V	910	910	910
Frequency (Hz)		50	50	50
Water displacement (m ³ /h)		2.9	3.4	4.12
Noise level (dB (A))		62	62	62
Heater size & weight information				
Weight (kg)		124	138	149
Height (cm)		105	107	109
Length (cm)		140.5	140.5	140.5
Width (cm)		114.5	114.5	114.5

The policy of Roxell is one of continuous product improvement. We reserve the right to alter specifications without prior notice. Heating products should be installed only in accordance with local laws, codes and regulations. These products are not for residential use, for agricultural use only. Gas pipe layout assistance is available to customers through authorized distributors. Specific, certified models are available for various countries, where required. Customer/ distributor need to check if Roxell has a certified model for the country of installation. All models meet stringent standards for low carbon monoxide.