

Model	80	100
Nominal load (kW)	88.23	103.5
Heat capacity (kW)	80.39	94.6
Air volume (m <sup>3</sup> /h)	10,111	10,111
Gas consumption G31 (kg/h)	6.41	8.24
Gas type G31	propane	propane
Gas consumption G20 (m <sup>3</sup> /h)	9.13	11.19
Gas type G20	natural gas	natural gas
Gas consumption G25 (m <sup>3</sup> /h)	10.35	13.01
Gas type G25	natural gas	natural gas
Power consumption (W)	1505	1505
Supply voltage (V)	230	230
Current (A)	6.7	6.7
Rotation speed (RPM)	1390	1390
Frequency (Hz)	50	50
Air throw (m)	36	36
<b>Heater size &amp; weight information</b>		
Weight per complete unit (kg)	298	298
Height (mm) – without legs	1007	1007
Length (mm)	1370	1370
Width (mm)	2003	2003
<b>Minimum clearance to combustibles</b>		
Rear side of heater (mm)	750	750
Service side of heater (mm)	3000	3000
Above heater (mm)	-	-
Below heater (mm)	400	400

*The policy of Roxell is one of continuous product improvement. We reserve the right to alter specifications without prior notice. Heating products should be installed only in accordance with local laws, codes and regulations. These products are not for residential use, for agricultural use only. Gas pipe layout assistance is available to customers through authorized distributors. Specific, certified models are available for various countries, where required. Customer/ distributor need to check if Roxell has a certified model for the country of installation. All models meet stringent standards for low carbon monoxide.*