

Model		45	60	75	100
Nominal load (kW)		49	66	79	106
Heat capacity (kW)		44.6	60.9	73.1	96.5
Air volume (m <sup>3</sup> /h)	230 V	7180	8950	10950	13400
	400 V	6800	8650	10950	12950
Current (A)		2.3	2.5	3.3	6.8
Gas consumption G31 (kg/h)		3.8	5.2	6.2	8.2
Gas type G31		propane			
Gas consumption G20 (m <sup>3</sup> /h)		5.2	7	8.4	11.2
Gas type G20		natural gas			
Gas consumption G25 (m <sup>3</sup> /h)		6.03	8.12	9.74	13.01
Gas type G25		natural gas			
Power consumption (W)		533	583	753	1553
Supply voltage (V)		230			
Rotation speed (RPM)		1365	900	900	1320
Frequency (Hz)		50			
Air throw (m)		25	30	32	36
<b>Heater size &amp; weight information</b>					
Weight per complete unit (kg)		108	125	138	195
Height (cm)		87.5	87.5	87.5	98.4
Length (cm)		96.5	129.8	129.8	129.8
Width (cm)		104.2	110	103	110
<b>Minimum clearance to combustibles</b>					
Rear side of heater (cm)		15			
Service side of heater (cm)		50			
Above heater (cm)		70			
Below heater (cm)		70-150			
Exhaust outlet (cm)		150			
Air inlet heater (cm)		150			
Air outlet heater (cm)		300			

*The policy of Roxell is one of continuous product improvement. We reserve the right to alter specifications without prior notice. Heating products should be installed only in accordance with local laws, codes and regulations. These products are not for residential use, for agricultural use only. Gas pipe layout assistance is available to customers through authorized distributors. Specific, certified models are available for various countries, where required. Customer/ distributor need to check if Roxell has a certified model for the country of installation. All models meet stringent standards for low carbon monoxide.*

Model	45	60	75	100
Nominal load (kW)	49	66	79	106
Heat capacity (kW)	44.6	60.9	73.1	96.5
Air volume (m <sup>3</sup> /h)	5800	7000	8670	10800
Current (A)	2.3	2.5	3.3	6.8
Gas consumption G31 (kg/h)	3.8	5.2	6.2	8.2
Gas type G31	propane			
Gas consumption G20 (m <sup>3</sup> /h)	5.2	7	8.4	11.2
Gas type G20	natural gas			
Gas consumption G25 (m <sup>3</sup> /h)	6	8.1	9.7	13
Gas type G25	natural gas			
Power consumption (W)	533	583	753	1553
Supply voltage (V)	230			
Rotation speed (RPM)	1365	900	900	1320
Frequency (Hz)	50			
Air throw (m)	15*			
<b>Heater size &amp; weight information</b>				
Weight per complete unit (kg)	108	125	167	195
Height (cm)	136.2	141.5	134.7	157
Length (cm)	96.5	129.8	129.8	129.8
Width (cm)	84.5	84.5	84.5	95.4
<b>Minimum clearance to combustibles</b>				
Sides of heater (cm)	300			
Above heater (cm)	70			
Below heater (cm)	70-150			
Exhaust outlet (cm)	150			
Air inlet heater (cm)	150			
Air outlet heater (cm)	300			

*The policy of Roxell is one of continuous product improvement. We reserve the right to alter specifications without prior notice. Heating products should be installed only in accordance with local laws, codes and regulations.*

*These products are not for residential use, for agricultural use only. Gas pipe layout assistance is available to customers through authorized distributors. Specific, certified models are available for various countries, where required. Customer/ distributor need to check if Roxell has a certified model for the country of installation.*

*All models meet stringent standards for low carbon monoxide.*

*\*15 m radius in all directions, horizontally.*