

Feeding system for weaners, finishing pigs and wean-to-finish pigs	Blu'Hox® 30	Blu'Hox® 145	Blu'Hox® W2F (*)
Number of pigs per pan			
- in relation to feeding places	max. 12 pigs per feeding place		
- In relation to drinking places	max. 15 pigs per drinking place (**)		
- Roxell advice, economic optimum	7 pigs per feeding place		
Minimum start weight for each individual pig (lb)	11	44	11
Maximum end weight for each individual pig (lb)	66	320	320
Number of feeding places	6	6	6
Number of nipples per pan	4	4	4
Nipple flow capacity (gal/min) (recommended)	0.11–0.13	0.21–0.26	0.11–0.26 (***)
Hopper capacity / with extension (gal) Weight (lb) (****)	19/40 99/220	19/40 99/220	19/40 99/220
Blu'Hox™ (hopper edge) height (ft) 154/331	3.35/3.97	4.10/4.89	4.10/4.89
Minimum pen width:			
- Blu'Hox® in center (ft)	6.89	13.12	13.12
- Blu'Hox® in fence (ft)	3.44	6.56	6.56
Assembly time Blu'Hox® (min): 1 skilled person/Blu'Hox® (*****)	20	20	20
Flushing	no	no	no
Anchoring positions	4	4	4

(\*) With adjustable drinking system

(\*\*) If more than 15 pigs per drinking place, consider placing extra drinkers in the pen.

(\*\*\*) In combination with water control panel 04305358

(\*\*\*\*) Specific weight: 41.8 lb/ft<sup>3</sup>

(\*\*\*\*\*) Not included: installation time in pens and water supply

Feeding system for weaners and finishing pigs	Blu'Hox <sup>®</sup> 30 <sup>+</sup> /45 <sup>+</sup>	Blu'Hox <sup>®</sup> 120 <sup>+</sup> /145 <sup>+</sup>
Number of pigs per pan		
- in relation to feeding places	max. 12 pigs per feeding place	
- In relation to drinking places	max. 15 pigs per drinking place (*)	
- Roxell advice, economic optimum	7 pigs per feeding place	
Minimum start weight for each individual pig (lb)	11	44
Maximum end weight for each individual pig (lb)	66/99	265/320
Number of feeding places	10/10	10/8
Number of nipples per pan	6/6	6/8
Number of nipples per pan + DRY-WET	4 + 2	4 + 2 / -
Nipple flow capacity (gal/min) (recommended) – DRY-WET	0.13-0.19	0.21-0.29
Nipple flow capacity (gal/min) (recommended)	0.13-0.19	0.21–0.29
Hopper capacity / with extension (gal) Weight (lb) (**)	19/40 99/220	19/40 99/220
Blu'Hox <sup>™</sup> (hopper edge) height (ft) 154/331	3.61/4.10	4.10/4.76
Minimum pen width:		
- Blu'Hox <sup>®</sup> in center (ft)	6.9/8.2	13.1
- Blu'Hox <sup>®</sup> in fence (ft)	3.4/3.9	4.9/6.6
Assembly time Blu'Hox <sup>®</sup> (min): 1 skilled person/Blu'Hox <sup>®</sup> (***)	35	35
Flushing	yes	yes
Anchoring positions	3/4	3/4

(\*) If more than 15 pigs per drinking place, consider placing extra drinkers in the pen.

(\*\*) Specific weight: 41.8 lb/ft<sup>3</sup>

(\*\*\*) Not included: installation time in pens and water supply