

High capacity fan (unassembled 07101000 or pre-assembled 07101008)

Power	230 V 60 Hz 1 Phase		
Static pressure (Pa)	Free air	25	37
Airflow (CMH)	57,500	52,000	48,600
Airflow efficiency (CMH/W)	42.0	33.5	30.0
Airflow ratio	0.83		
Bess Lab	21280		

High capacity fan (unassembled 07101032 or pre-assembled 07101040)

Power	230 V 50 Hz 3 Phase		
Static pressure (Pa)	Free air	25	37
Airflow (CMH)	56,800	51,400	45,500
Airflow efficiency (CMH/W)	42.7	34.1	27.9
Air flow ratio	0.77		
Bess Lab	21285		

High capacity fan (unassembled 07101032 or pre-assembled 07101040)

Power	230 V 60 Hz 3 Phase		
Static pressure (Pa)	Free air	25	37
Airflow (CMH)	57,200	51,400	45,800
Airflow efficiency (CMH/W)	42.9	34.1	28.1
Air flow ratio	0.77		
Bess Lab	21284		

High capacity fan (unassembled 07101080 or pre-assembled 07101064)

Power	400 V 50 Hz 3 Phase		
Static pressure (Pa)	Free air	25	37
Airflow (CMH)	55,500	50,300	47,500
Airflow efficiency (CMH/W)	40.9	33.4	30.1
Air flow ratio	0.83		
Bess Lab	22449		

The policy of Roxell is one of continuous product improvement. We reserve the right to alter specifications without prior notice.

Customer/ distributor need to check if Roxell has a certified model for the country of installation.

All models meet stringent standards for low carbon monoxide.

High efficiency fan (unassembled 07101016 or pre-assembled 07101024)

Power	230 V 60 Hz 1 Phase		
Static pressure (Pa)	Free air	25	37
Airflow (CMH)	51,600	45,800	42,200
Airflow efficiency (CMH/W)	45.6	36.5	31.9
Airflow ratio	0.778		
Bess Lab	22219		

High efficiency fan (unassembled 07101048 or pre-assembled 07101056)

Power	230 V 50 Hz 3 Phase		
Static pressure (Pa)	Free air	25	37
Airflow (CMH)	52,300	46,300	42,700
Airflow efficiency (CMH/W)	47.1	37.2	32.9
Air flow ratio	0.784		
Bess Lab	22198		

High efficiency fan (unassembled 07101048 or pre-assembled 07101056)

Power	230 V 60 Hz 3 Phase		
Static pressure (Pa)	Free air	25	37
Airflow (CMH)	51,800	46,000	42,200
Airflow efficiency (CMH/W)	45.6	36.8	32.2
Air flow ratio	0.775		
Bess Lab	22447		

High efficiency fan (unassembled 07101088 or pre-assembled 07101072)

Power	400 V 50 Hz 3 Phase		
Static pressure (Pa)	Free air	25	37
Airflow (CMH)	51,900	45,800	42,300
Airflow efficiency (CMH/W)	46.4	36.7	32.4
Air flow ratio	0.779		
Bess Lab	22448		

The policy of Roxell is one of continuous product improvement. We reserve the right to alter specifications without prior notice.

Customer/ distributor need to check if Roxell has a certified model for the country of installation.

All models meet stringent standards for low carbon monoxide.