

| Model                                       | 50              | 60              | 70              |
|---|-----------------|-----------------|-----------------|
| Supply/return water temperature (°F)        | 176/149         | 176/149         | 176/149         |
| Air volume (CFM)                            | 4355            | 4355            | 4355            |
| Current (A)                                 | 1.2             | 1.2             | 1.2             |
| Power consumption (W)                       | 534             | 534             | 534             |
| Supply voltage (V)                          | 1x230/<br>3x400 | 1x230/<br>3x400 | 1x230/<br>3x400 |
| Rotation speed (RPM)                        | 920             | 920             | 920             |
| Frequency (Hz)                              | 50/60           | 50/60           | 50/60           |
| Water displacement (CFM)                    | 1.71            | 2.0             | 2.42            |
| Noise level (dB (A))                        | 62              | 62              | 62              |
| <b>Heater size &amp; weight information</b> |                 |                 |                 |
| Weight (lb)                                 | 273.4           | 304.2           | 328.5           |
| Height (in)                                 | 41.3            | 42.13           | 42.91           |
| Length (in)                                 | 55.31           | 55.31           | 55.31           |
| Width (in)                                  | 45.08           | 45.08           | 45.08           |

*The policy of Roxell is one of continuous product improvement. We reserve the right to alter specifications without prior notice. Heating products should be installed only in accordance with local laws, codes and regulations. These products are not for residential use, for agricultural use only. Gas pipe layout assistance is available to customers through authorized distributors. Specific, certified models are available for various countries, where required. Customer/ distributor need to check if Roxell has a certified model for the country of installation. All models meet stringent standards for low carbon monoxide.*