

Model		40	70	100	120
Nominal load (kW)		40	70	98	119
Air volume (m ³ /h)		3800	5000	6500	6500
Current (A)	50 Hz	1.3	2.3	2.9	2.9
	60 Hz	1.9	3.2	4	4
Gas consumption G31 (kg/h)		2.9	5.4	6.5	8.1
Gas type G31		propane			
Gas consumption G20 (m ³ /h)		3.8	6.5	9.45	11.4
Gas type G20		natural gas			
Gas consumption G25 (m ³ /h)		4.5	7.76	11.08	13
Gas type G25		natural gas			
Power consumption (W)	50 Hz	265	480	620	620
	60 Hz	312	657	850	850
Supply voltage (V)		230			
Rotation speed (RPM)	50 Hz	1400	1290	1350	1350
	60 Hz	1638	1509	1650	1650
Frequency (Hz)		50/60			
Air throw (m)		35	35	40	40
Heater size & weight information					
Weight per complete unit (kg)		32	42	48	48
Height (cm)		50	58	62.4	62.4
Length (cm)		100	110.5	115.2	115.2
Width (cm)		55	63.7	68.9	68.9
Minimum clearance to combustibles					
Sides of heater (cm)		100			
Air inlet heater (cm)		100			
Air outlet heater (cm)		300			

The policy of Roxell is one of continuous product improvement. We reserve the right to alter specifications without prior notice. Heating products should be installed only in accordance with local laws, codes and regulations. These products are not for residential use, for agricultural use only. Gas pipe layout assistance is available to customers through authorized distributors. Specific, certified models are available for various countries, where required. Customer/ distributor need to check if Roxell has a certified model for the country of installation. All models meet stringent standards for low carbon monoxide.

Model	8 l	10 l	12 l
Nominal load (kW)	80	100	120
Air volume (m ³ /h)	7700		
Current (A)	5.1		
Fuel consumption (l/h)	8	9.6	12
Fuel type	oil		
Power consumption (W)	1150		
Supply voltage (V)	230		
Rotation speed (RPM)	1400		
Frequency (Hz)	50/60		
Air throw (m)	40		
Heater size & weight information			
Weight per complete unit (kg)	47	47	65
Height (cm)	59.1	59.1	59.1
Length (cm)	126.8	126.8	136.8
Width (cm)	66.4	66.4	66.4
Minimum clearance to combustibles			
Sides of heater (cm)	100		
Air inlet heater (cm)	100		
Air outlet heater (cm)	300		

The policy of Roxell is one of continuous product improvement. We reserve the right to alter specifications without prior notice. Heating products should be installed only in accordance with local laws, codes and regulations. These products are not for residential use, for agricultural use only. Gas pipe layout assistance is available to customers through authorized distributors. Specific, certified models are available for various countries, where required. Customer/ distributor need to check if Roxell has a certified model for the country of installation. All models meet stringent standards for low carbon monoxide.