

Feeding system for weaners, finishing pigs and wean-to-finish pigs	Blu'Hox <sup>®</sup> 30	Blu'Hox® 145	Blu'Hox® W2F (*)
Number of pigs per pan			
- in relation to feeding places	max. 12 pigs per feeding place		
- In relation to drinking places	max. 15 pigs per drinking place (**)		
- Roxell advice, economic optimum	7 pigs per feeding place		
Minimum start weight for each individual pig (kg)	5	20	5
Maximum end weight for each individual pig (kg)	30	145	145
Number of feeding places	6	6	6
Number of nipples per pan	4	4	4
Nipple flow capacity (I/min) (recommended)	0.5–0.7	0.8–1.1	0.5–1.1 (***)
Hopper capacity / with extension (I) Weight (kg) (****)	70/150 45/100	70/150 45/100	70/150 45/100
Blu'Hox™ (hopper edge) height (m) 70/150	1.02/1.21	1.25/1.49	1.25/1.49
Minimum pen width:			
- Blu'Hox® in center (m)	2.1	4	4
- Blu'Hox® in fence (m)	1.05	2	2
Assembly time Blu'Hox™ (min): 1 skilled person/Blu'Hox™ (*****)	20	20	20
Flushing	no	no	no
Anchoring positions	4	4	4

<sup>(\*)</sup> With adjustable drinking system

<sup>(\*\*)</sup> If more than 15 pigs per drinking place, consider placing extra drinkers in the pen.

<sup>(\*\*\*)</sup> In combination with water control panel 04305358

<sup>(\*\*\*\*)</sup> Specific weight: 0.67 kg/dm<sup>3</sup>

<sup>(\*\*\*\*\*)</sup> Not included: installation time in pens and water supply



Feeding system for weaners and finishing pigs	Blu'Hox™ 30⁺/45⁺	Blu'Hox™ 120⁺/145⁺
Number of pigs per pan		
- in relation to feeding places	max. 12 pigs per feeding place	
- In relation to drinking places	max. 15 pigs per drinking place (*)	
- Roxell advice, economic optimum	7 pigs per feeding place	
Minimum start weight for each individual pig (kg)	5	20
Maximum end weight for each individual pig (kg)	30/45	120/145
Number of feeding places	10/10	10/8
Number of nipples per pan	6/6	6/8
Number of nipples per pan + DRY-WET	4 + 2	4 + 2 / -
Nipple flow capacity (I/min) (recommended)	0.5-0.7	0.8-1.1
Nipple flow capacity (I/min) (recommended) – DRY-WET	0.5–0.7	0.8–1.1
Hopper capacity / with extension (I) Weight (kg) (**)	70/150 45/100	70/150 45/100
Blu'Hox™ (hopper edge) height (m) 70/150	1.10/1.25	1.25/1.45
Minimum pen width:		
- Blu'Hox® in center (m)	2.1/2.5	4
- Blu'Hox <sup>®</sup> in fence (m)	1.05/1.2	1.50/2
Assembly time Blu'Hox® (min): 1 skilled person/Blu'Hox® (***)	35	35
Flushing	yes	yes
Anchoring positions	3/4	3/4

<sup>(\*)</sup> If more than 15 pigs per drinking place, consider placing extra drinkers in the pen.

<sup>(\*\*)</sup> Specific weight: 0.67 kg/dm³

<sup>(\*\*\*)</sup> Not included: installation time in pens and water supply